

**THE EFFECT OF SPIN COATING RATE ON MORPHOLOGY AND OPTICAL PROPERTIES OF CUPROUS OXIDE THIN FILM PREPARED BY SOL-GEL TECHNIQUE**

D. S. C. Halin, I. A. Talib, A. R. Daud and M. A. A. Hamid  
School of Applied Physics, Faculty of Science and Technology  
Universiti Kebangsaan Malaysia, 43600 UKM Bangi, Selangor, Malaysia

**ABSTRACT**

Cuprous oxide thin films were successfully grown on indium tin oxide (ITO) coated glass by sol-gel spin coating using diethanolamine (DEA) as a solubility agent. The films were annealed at 350 °C in 5% H<sub>2</sub> + 95% N<sub>2</sub> atmosphere. The films were characterized by X-ray diffraction (XRD), scanning electron microscopy (SEM) and ultraviolet-visible (UV-vis) spectroscopy. The effect of spinning rate on deposition on the microstructure, thickness and optical properties of cuprous oxide films was investigated. Based on the SEM micrographs of the as obtained films, we found that the grain size decreases with the increase in spinning rate. At the rate of 6000 rpm, the film shows better coverage with the rounded shape grain size is about 45 nm. Optical absorbance of the films was in the regions of 400-800 nm wavelengths. The optical band gap values of the films are in the range of 2.0-2.2 eV.

<http://journal.masshp.net/wp-content/uploads/Journal/2009/Jilid%201/D.%20S.%20C.%20Halin%20119-125.pdf>

**REFERENCES**

- [1]. T. J. Richardson, J. L. Slack, M. D. Rubin (2000). Electrochromism in copper oxide thin films. In: Presented at the 4th international meeting on electrochromism, pages 1-6, Uppsala, Sweden, August 2000.
- [2]. A. A. Ogwu, E. Bouquerel, O. Ademosu, S. Moh, E. Crossan, F. Placido (2005). An investigation of the surface energy and optical transmittance of copper oxide thin films prepared by reactive magnetron sputtering. *Acta Materialia* 53, 5151-5159.
- [3]. B.P. Rai (1988). Cu<sub>2</sub>O solar cells: A review. *Solar Cells* 25, 265-272.
- [4]. T. Mahalingam, J. S. P. Chitra, S. Rajendran, M. Jayachandran, M. J. Chockalingam (2000). Galvanostatic deposition and characterization of cuprous oxide thin films. *J. Cryst. Growth* 216, 304-310.
- [5]. Y. Qu, X. Li, G. Chen, H. Zhang, Y. Chen (2008). Synthesis of Cu<sub>2</sub>O nano-whiskers by a novel wet-chemical route. *Mater. Lett.* 62, 886-888.
- [6]. B. Balamurugan, B. R. Mehta (2001). Optical and structural properties of nanocrystalline copper oxide thin films prepared by activated reactive evaporation. *Thin Solid Films* 396, 90-96.
- [7]. L. Armelao, D. Barreca, M. Bertapelle, G. Bottaro, C. Sada, E. Tondello (2003). A sol-gel approach to nanophasic copper oxide thin films. *Thin Solid Films* 442, 48-52.
- [8]. D. S. C. Halin, I. A. Talib, M. A. A. Hamid, A. R. Daud (2008). Characterization of cuprous oxide thin films on n-Si substrate prepared by sol-gel spin coating. *J. Solid State Science & Technology* 16, 232-237.
- [9]. R. Dewi, N. I. Baa'yah, I. A. Talib (2007). The effect of spin coating rate on the microstructure, grain size, surface roughness and thickness of Ba<sub>0.6</sub>Sr<sub>0.4</sub>TiO<sub>3</sub> thin film prepared by the sol-gel process. *Materials Science-Poland* 25, 658-662.

- [10]. K.H. Yoon, W.J. Choi, D.H. Kang (2000). Photoelectrochemical properties of copper oxide thin films coated on an *n*-Si substrate. *Thin Solid Films* **372**, 250-256.
- [11]. R.F. Roberts (1974). X-ray photoelectron spectroscopic characterization of copper oxide surfaces treated with benzotriazole. *J. Electron. Spectrosc. Relat. Phenom.* **4**, 273-291.
- [12]. Ray S. C. (2001). Preparation of copper oxide thin film by the sol-gel-like dip technique and study of their structural and optical properties. *Solar Energy Material & Solar Cells* **68**, 307-312.
- [13]. M. T. S. Nair, L. Guerrero, O. L. Arenas and P. K. Nair (1999). Chemically deposited copper oxide thin films: structural, optical and electrical characteristics. *Appl. Surf. Sci.* **150**,143-151.