

**DIELECTRIC PROPERTIES OF STRONTIUM TITANATE IN THE
1 MHZ TO 1.5 GHZ FREQUENCY REGIONS**

Wong Swee Yin, Jumiah Hassan and Mansor Hashim
*Physics Department, Faculty of Science, Universiti Putra Malaysia,
43400 Serdang, Selangor, Malaysia*

ABSTRACT

Strontium Titanate, SrTiO₃ samples were prepared using the conventional solid state reaction method. SrTiO₃ samples were sintered at 1100°C, 1200°C, and 1300°C. XRD was used to determine the crystalline structure of the samples. The AFM showed the grain size was significantly increased with an increase in sintering temperatures. The dielectric properties of the sample were measured using Agilent 4291B Impedance/material Analyzer in the sub-microwave region in the frequency range 1 MHz to 1.5 GHz at room temperature. The dielectric constant and the average grain size were found to be the highest for the SrTiO₃ sample sintered at 1200°C. Hence, greatest dielectric polarization occurred in the sample with the largest grain size.

<http://journal.masshp.net/wp-content/uploads/Journal/2009/Jilid%201/Wong%20Swee%20Yin%2057-62.pdf>

REFERENCES

- [1]. Hiroyuki Ishikawa, Kouya Oohira, Tatsuo Nakajima, Tomohiro Akiyama, (2008) *Journal of Alloys and Compounds* **454** 384–388.
- [2]. J. Petzelt, I. Gregora, I. Rychetsky, T. Ostapchuk, S. Kamba, P. Vanek, Y. Yuzyuk, A. Almeida, M.R. Chavez, B. Gorshunov, M. Dressel, S. Hoffmann-Eifert, R. Waser, (2001) *Journal of the European Ceramic Society* **21** 2681–2686.
- [3]. S. Kamba, D. Noujni, A. Pashkin, J. Petzelt, R.C. Pullar, A.-K. Axelsson, N. McN Alford, (2006) *Journal of the European Ceramic Society* **26** 1845–1851.
- [4]. I. Burn, S. Neirman, (1982) *Journal of Materials Science* **17** 3510-3524